

**EZYCOAT SMOOTH Roll on****DESCRIPTION AND COMPOSITION**

**Ezycoat Smooth Roll On** is a low profile style roll on texture paint. It offers a uniform and highly flexible finish while also providing an aesthetically pleasing finish that can hide many imperfections that may exist in a surface. Ezycoat Roll On is ideal for application over precast concrete surfaces or is an excellent substitute for areas that do not require rendering or where cement render is just not in the budget.

Ezycoat Smooth Roll On unlike many of the other texture paint finishes produces a regular off the roller finish which is consistent as the name suggests & smooth in appearance. The intensity of the roll pattern can be adjusted by the use of different texture roller sleeves.

**USE**

**Ezycoat Smooth Roll On** is a specially designed pigmented coating system for application over such products as EzySkim Render, Ezyump, ECA, Super 6 and Conventional Render. **Ezycoat Smooth Roll On** is suitable for application over precast concrete and flush finished brick & blockwork .

The final product will produce a protective decorative coating that is durable, water resistant and highly wear and U.V. resistance. It's extra thick film forming ability and properties enable **Ezycoat Smooth Roll On** to maintain excellent transpiration properties.

**APPLICATION**

Prior to application of the **Ezycoat Smooth Roll On** to a surface it is essential that the surface be free of any contaminants that may affect the performance of the textured paint system. The coating sequence must follow the application specification sequence in Table 1.



**Table 1:- Ezycoat Textured Paint Finishes**

Application Specification Sequence over Ezycoat Render, Masonry or precast Concrete surfaces

Coating Sequence	Product
Coating 1.	1 Coat Ezycoat Masonry Sealer Drying time 2 hrs
Coating 2.	1 <sup>st</sup> Coat Ezycoat Smooth Roll On Drying time before recoat 5-6 hrs depending on weather conditions
Coating 3.	2 <sup>nd</sup> Coat Ezycoat Membrane Full cure at 12 Hours after completion depending on weather conditions.

*\* With some darker colours it may be necessary to apply an extra coat of Ezycoat Membrane in order to Maintain long term colour and required DFT. This will be at the discretion of the Painting Contractor to determine or if in doubt contact our offices for further advice.*

It is recommended that the process of cutting in, be carried out at the same time as rolling or applying the **Ezycoat Smooth Roll On** on the walls so as to maintain a wet on wet application. This will reduce the effect of application marks on the wall. Always try to apply **Ezycoat Smooth Roll On** in shaded areas out of direct sunlight.

**Table 2 – Ezycoat Smooth Roll On Properties Table**

<b>Consumption 15 Lit. Pail</b>	<b>40 to 45 sqm</b>	<b>Application by long nap roller followed with woolen Mit.</b>
<b>Base</b>	<b>Water</b>	<b>Wash up in water</b>
<b>Curing Time</b>	<b>12 Hrs</b>	<b>Depending on weather conditions</b>
<b>Colour</b>	<b>Various-Tintable</b>	<b>Colours available on request</b>
<b>Classification</b>	<b>Non Hazardous</b>	

Due to the many different proprietary building systems available on the market, it is highly recommended that you contact our offices and request a copy of the Ezycoat specification for the building system you are using. **EZYBUILD SPECS** are readily available upon request either from our company representatives or our offices.

For more detailed information with regards this product and any safety concerns, please refer to the Material Safety Data Sheets available from Active Building Systems Pty Ltd upon request.

**Note:**

**Ezycoat Smooth Roll On** should not be applied at temperatures below 7°C or when there is the possibility of rain. The durability of the product in its original confection is guaranteed for 1 year as long as it is not exposed to direct sunlight or temperatures below 4 degrees.

**Ezycoat Smooth Roll On** is not suitable for use in areas prone to water logging, submersion, continually damp and/or below ground. Walls where **Ezycoat Smooth Roll On** is to be applied must be free draining. In the case of retaining walls the rear of the wall must be engineered to prevent any penetration of moisture or water through the wall in to the rear of the **Ezycoat Smooth Roll On**. Failure to do so will result in damage to the **Ezycoat Smooth Roll On** and is not covered by warranty.

For more detailed information with regards this product and safety issues, please refer to the Material Safety Data Sheets available from Active Building Systems Pty Ltd upon request.

**Ezycoat Smooth Roll On** are to be applied only by trades persons holding a license for this trade as recognised by the legislative building authority for the relevant state to which the work is being carried out. Misuse of this product and/or noncompliance with technical specifications will void any warranties whether verbal or written.

Active Building Systems Pty Ltd reserves the right to change, update and republish these specifications without any notice. It is the user's responsibility to attain the most current publication of Ezycoat Specifications from Active Building Systems Pty Ltd.

