

EUROSTYLE VENETIAN**DESCRIPTION AND COMPOSITION**

Eurostyle Venetian is a high end quality decorative finishing plaster. It has been specially formulated to act as a Smooth Finishing plaster that reproduces the Smooth high gloss or Matt finishes that are usually reserved for the European market. Using the latest in product technology we have been able to produce a product that will retain all the physical properties needed for our harsh Australian conditions and yet retain the quality reserved for these types of finishes. Eurostyle Venetian is suitable for use over suitably prepared plasterboard, Fibre cement precast concrete and rendered surfaces.

USE

Eurostyle Venetian is suitable for Exterior Or Interior application over a variety of suitably prepared building mediums such as Concrete Block, Brick, Fibre cement, Plasterboard and precast concrete surfaces. Using a specific finishing technique and a series of applications based on the quality of the base medium, the Eurostyle Venetian can be finished to provide a high gloss lustre or can be left in a more natural state depending on the application process adopted. In order to allow the Eurostyle Venetian to maintain the finish as was intended for years to come, it is required that it be finished with the Eurostyle Gloss or Matt Sealer or the Cera Finish (Refer to Product TDS.). In order to achieve the best finish possible, we highly recommend that the applicator undergo a training course or a demonstration to understand the true behavioural properties of the Eurostyle Finish Range, contact our offices for further information.

APPLICATION

Eurostyle Venetian is a speciality product that has specific requirements when it comes to application. Prior to commencing any application process always ensure that the building medium to which the Eurostyle Venetian is to be applied has been installed to manufacturers specifications, if in doubt always refer the matter back to the client or builder for further consideration before commencing. The applying surface must be sealed using Eurostyle Base Sealer (Refer to TDS.) prior to commencement of application. Always ensure that the applying surface is free of any contaminants or free dust that may impede the performance of the coating system. If in doubt, please contact our offices for further advice. The Eurostyle Venetian must be mixed thoroughly with a mechanical mixer before use. Do not add water to the Eurostyle Venetian and always ensure the drum is sealed correctly after use, otherwise the product will dry out not be suitable for further use.

The application process should be done using high-quality stainless-steel Venetian trowels available from Active Building Systems. The application process of the Eurostyle Venetian is split into a 2 to 3 coating application process depending on the end finish that needs to be achieved and the quality of the original surface to which it is to be applied. refer Table 1. The method of application is very important in order to achieve the desired finish. It is the responsibility of the product applicator to ensure they have had suitable training in the application of the product before attempting to use the product. Training & Demonstrations are available on request.

Sequence	Product Description	Method (Refer to Training Guide)	Coverage
#1	Eurostyle Base Sealer	Roll on with medium nap roller	Even spread 60 to 80 sqm/15Lt.
#2	Eurostyle Venetian	Venetian application Trowel	Approx. 4 sqm/Lit.
#3	Eurostyle Venetian	<u>Option 1.</u> If Surface is satisfactory then #3 shall be the finishing coat. Apply with Venetian Trowel allow to partially dry then finish with Venetian Burnishing Trowel. Then proceed to #5. <u>Option 2.</u> If surface is still not satisfactory then apply coat #3 with venetian trowel and level off (Do not Burnish)for sequence #4	Approx. 4 sqm/Lit.
#4	Eurostyle Venetian	Venetian Trowel Application allow to partially dry then finish with the Venetian Burnishing Trowel if a polished look is required otherwise do not Burnish for a rustic finish.	Approx. 4 sqm/Lit.
#5	Eurostyle Gloss/Matt Sealer	Roll on with medium nap roller	Even spread 60 to 80 sqm/15Lt.

- Note/s:- The process of Burnishing the Eurostyle Venetian must only be carried out on the final application process. Do not carry out the process of Burnishing on intermediate coats as this will not allow for any subsequent coats to be easily finished and will impede the final finish. Substrates must contain no more than 15% moisture (WME) before application can commence.

Table 1.

DATA

Consumption:	Consumption may varying depending on condition of surface. Typically 4 sqm/Ltr.
Dry Film	approx. 0.5mm
Bag Size:	4 & 15 Litre Pails
Classification:	non-Hazardous goods Low Voc.
Colours:	Natural White (Tint colour Range Available)
Drying Time	12 Hours @25° C & 50% relative Humidity
Safety Data	Refer to Ezycoat Eurostyle Venetian SDS.



Important Notes:	Do not apply in temperatures below 5 degrees Celsius or 24 hrs. prior to or after wet & rainy conditions. Do not apply in moist conditions. All walls must be free of moisture prior to application with a WME of no more than 15%. All surfaces should be cleaned and free of any contaminant, releasing agent, fungal growth which may affect the performance of these coatings. Any imperfections which may become visible in the finished surface should be patched and levelled with Ezycoat Patching compounds. Any structural imperfections and/or cracks will need to be stabilised prior to any further applications. The durability of the product in its original confection is guaranteed for 8 months as long as it is not exposed to direct sunlight or temperatures below 6 degrees. Eurostyle Venetian is not suitable for use in areas prone to water logging, submersion, continually damp and/or below ground. Walls where Eurostyle Venetian is to be applied must be free draining. In the case of retaining walls the rear of the wall must be engineered to prevent any penetration of moisture or water through the wall in to the rear of the Eurostyle Venetian. Failure to do so will result in damage to the Eurostyle Venetian and is not covered by warranty. Excess Waste product should be disposed of in a responsible manner following guidelines as set out by the local council's by-laws and Waste Disposal Procedures. For further safety Data refer to Ezycoat SDS for this product available from our offices & website.
-------------------------	--

Disclaimer

Due to the many different proprietary building systems available on the market, it is highly recommended that you contact our offices and request a copy of the Ezycoat specification for the building system you are using. **EZYBUILD SPECS** are readily available upon request either from our company representatives or our offices. For more detailed information with regards this product and any safety concerns, please refer to the Safety Data Sheets available from Active Building Systems Pty Ltd.

Eurostyle Venetian is to be applied by suitably licensed persons holding a license for this trade as recognised by the legislative building authority for the relevant state to which the work is being carried out and has undergone a training program in the use of these Eurostyle Finishes. Misuse of this product and/or noncompliance with technical specifications will void any warranties whether verbal or written. Active Building Systems Pty Ltd reserves the right to change, update and republish these specifications without any notice. It is the user's responsibility to attain the most current publication of Ezycoat Specifications from Active Building Systems Pty Ltd. Our goods come with guarantees that cannot be excluded under the Australian Consumer Laws.

