

EUROSTYLE BASE SEALER**DESCRIPTION AND COMPOSITION**

Eurostyle Base Sealer is an alkali resistant concentrated base sealer, specially formulated to prepare porous and non-porous uncoated surfaces for the application of the Eurostyle plaster finishes. Eurostyle Base sealer has been produced from a selected range of acrylic polyvinyl copolymers in a fluid emulsion that exhibit an excellent ability to penetrate surfaces while creating an stable base for the application of the smooth and refined products of the Eurostyle range of plaster finishes.

USE

Eurostyle Base Sealer is a quality sealer recommended for use on particularly porous surfaces characterized by high absorption, such as: concrete, concrete blocks, clay bricks/blocks, autoclaved aerated concrete (AAC), plasterboard, fibre cement, villa board, etc. It is ideal for its application over old plastered surfaces, so as to reinforce and stabilize the base, for the successive application of the Eurostyle finishing range of products.

Eurostyle Base Sealer may be applied by use of roller or brush. When applied it produces a lightly pigmented film which exhibits superior adhesion and sealing properties that allow the wall to transpire naturally whilst exhibiting water resistant properties.

APPLICATION

Prior to the application of the **Eurostyle Base Sealer**, all surfaces must be clean and free of dust or dirt, releasing agents and any loose paint on old surfaces must be removed to guarantee total adhesion between the Eurostyle Base Sealer and the applied surface.

Apply **Eurostyle Base Sealer** using a roller or brush so as to maintain even coverage and allow the surface to stand for approximately 4 to 8 hours before proceeding with any subsequent coatings.

DATA

Consumption:	Approximate Consumption Rate 5-8 sqm/Ltr Approx. Film build 60 micron. wet; 40 micron. (DFT)
Pail Size:	15Lit.
Classification:	non-hazardous goods/ non flammable
Colours:	White
Durability	Excellent abrasion resistance and cross linking ability
No. of coats required	1 coat application
Drying Time	Allow min. 4 hours to 8 Hrs dry @25° C & 50% relative Humidity
Safety Data	Refer to product SDS. Before use.
Important Notes:	Do not apply in temperatures below 5 degrees Celsius or 24 hrs prior to or after wet & rainy conditions. Do not apply in moist conditions. All walls must be free of moisture prior to application. All surfaces should be cleaned and free of any contaminant, releasing agent, fungal growth which may affect the performance of these coatings. Any imperfections which may become visible in the finished surface should be patched and leveled with Ezycoat Patching compounds. Any structural imperfections and/or cracks will need to be stabilised prior to any further applications. The durability of the product in its original confection is guaranteed for 1 year as long as it is not exposed to direct sunlight or temperatures below 6 degrees. Eurostyle Base Sealer is not suitable for use in areas prone to water logging, submersion, continually damp and/or below ground. Walls where Eurostyle Base Sealer is to be applied must be free draining. In the case of retaining walls the rear of the wall must be engineered to prevent any penetration of moisture or water through the wall in to the rear of the Eurostyle Base Sealer. Failure to do so will result in damage to the Eurostyle Base Sealer and is not covered by warranty. Excess Waste product should be disposed of in responsible manner following guidelines as set out by the local council's bi-laws and Waste Disposal Procedures.

Disclaimer

Due to the many different proprietary building systems available on the market, it is highly recommended that you contact our offices and request a copy of the Ezycoat specification for the building system you are using. **EZYBUILD SPECS** are readily available upon request either from our company representatives or our offices. For more detailed information with regards this product and any safety concerns, please refer to the Safety Data Sheets available from Active Building Systems Pty Ltd.

Eurostyle Base Sealer is to be applied by suitably licensed persons holding a license for this trade as recognised by the legislative building authority for the relevant state to which the work is being carried out and has undergone a training program in the use of these Eurostyle Finishes. Misuse of this product and/or noncompliance with technical specifications will void any warranties whether verbal or written. Active Building Systems Pty Ltd reserves the right to change, update and republish these specifications without any notice. It is the user's responsibility to attain the most current publication of Ezycoat Specifications from Active Building Systems Pty Ltd. Our goods come with guarantees that cannot be excluded under the Australian Consumer Laws.

