












# EZYCOAT

RENDER • TEXTURE • PAINT





## EZYCOAT RENDER RANGE

PRODUCT	APPLICATION TOOLS	FEATURE/BENEFIT	SAND GRADE	COVERAGE	RECOMMENDED COATING THICKNESS	POST APPLICATION
 <b>SKIM RENDER</b> Off White	Hawk & Steel Trowel Render Pump Sponge Float	Provides an even and consistent sand finish for use as a skim coat.	Medium Fine	3 - 4.8 m <sup>2</sup> /bag	2.5mm MIN - 5mm MAX per coat to a MAX thickness of 8mm	48 hour set time 7 day cure Max strength at 28 days
 <b>ECA RENDER</b> Off White	Hawk & Steel Trowel Render Pump Sponge Float	Designed for multi-purpose use including EPS systems, with the addition of polymer for superior bonding strength.	Medium Fine	3 - 4.8 m <sup>2</sup> /bag	2.5mm MIN - 5mm MAX per coat to a MAX thickness of 8mm	48 hour set time 7 day cure Max strength at 28 days
 <b>PUMP RENDER</b> Off White	Hawk & Steel Trowel Render Pump Sponge Float	Developed to cater for both hand and pump application.	Medium Coarse	3 - 4.8 m <sup>2</sup> /bag	2.5mm MIN - 5mm MAX per coat to a MAX thickness of 8mm	48 hour set time 7 day cure Max strength at 28 days
 <b>TRADITIONAL RENDER</b> Off White	Hawk & Steel Trowel Render Pump Sponge Float	A versatile and easy to use render with similar properties to traditional sand cement render.	Coarse	3 - 4.8 m <sup>2</sup> /bag	2.5mm MIN - 5mm MAX per coat to a MAX thickness of 8mm	48 hour set time 7 day cure Max strength at 28 days
 <b>EZYFLOAT RENDER</b> Off White	Hawk & Steel Trowel Sponge Float	Ideal for use under acrylic texture coatings.	Coarse	3 - 4.8 m <sup>2</sup> /bag	2.5mm MIN - 5mm MAX per coat to a MAX thickness of 8mm	48 hour set time 7 day cure Max strength at 28 days
 <b>EZYPREP &amp; PATCH</b> Off White	Steel Trowel	To prep and patch surfaces that would otherwise not accept a render product.	Fine	4 - 6 m <sup>2</sup> /bag	1.5mm MIN 3mm MAX	48 hour set time 7 day cure Max strength at 28 days
 <b>HIGH BUILD 40 RENDER</b> Off White	Steel Trowel	Used on surfaces that require additional build thickness.	Coarse	0.5 - 1 m <sup>2</sup> /bag	10mm MIN 20mm MAX	48 hour set time 7 day cure Max strength at 28 days


## TEXTURE FINISHES

PRODUCT	APPLICATION TOOLS	FEATURE/BENEFIT	SAND GRADE	COVERAGE	DRY TIME (SET TIME)
 <b>SAND 800</b>	Steel Trowel Plastic Float	A preblended acrylic texture that produces a granular sand finish style.	Medium	11 - 12 m <sup>2</sup> /pail	Approx. 48 hours
 <b>MIAMI</b>	Steel Trowel Plastic Float	A mineral feature texture with the added protection of REPEL hydrophobic technology.	Medium	11 - 12 m <sup>2</sup> /pail	Approx. 48 hours
 <b>POLYMER RENDER</b>	Steel Trowel Plastic Float	A medium-fine acrylic scrub fine sand finish.	Fine	7 - 10 m <sup>2</sup> /pail	Approx. 48 hours
 <b>SCRATCH 2MM</b>	Steel Trowel Plastic Float	Decorative acrylic texture designed to produce a classic vertical or swirl finish.	Coarse Scratch	6 - 10 m <sup>2</sup> /pail	Approx. 48 hours
 <b>BASEFLEX</b>	Steel Trowel Plastic Float	A granular base levelling coat or medium-coarse granular texture.	Coarse	3 - 5 m <sup>2</sup> /pail/coat	Approx. 48 hours

## SEALERS AND TOPCOATS

PRODUCT	APPLICATION TOOLS	FEATURE/BENEFIT	COVERAGE	DRY TIME (SET TIME)
 <b>MASONRY SEALER</b>	Roller Brush	Preparatory sealer and aid to subsequent texture application in EZYCOAT systems.	100 - 120 m <sup>2</sup> /pail/coat	4 hours
 <b>ULTRAFINE SEALER</b>	Roller Brush	Preparatory sealer and aid to subsequent texture application in EZYCOAT systems.	70 - 85 m <sup>2</sup> /pail per coat	4 hours
 <b>CEILING TEXTURE INT/EXT</b>	Texture Roller, Mop Finish Brush	A roll on stipple texture ideal for off-form concrete ceiling and soffits.	20 - 25 m <sup>2</sup> /pail/coat	4 hours
 <b>MEMBRANE</b>	MIN 24mm Long Nap Roller Brush	A durable and flexible membrane paint designed to protect your EZYCOAT render & texture systems.	50 - 60 m <sup>2</sup> /pail per coat 2 coats recommended	4 hours

## PATCHES

PRODUCT	APPLICATION TOOLS	FEATURE/BENEFIT	SAND GRADE	PATCH DEPTH	DRY TIME (SET TIME)
 <b>PATCH</b>	Steel Trowel Sponge	Acrylic basecoat designed to patch and prepare masonry surfaces in EZYCOAT systems.	Smooth	2mm	12 hours MIN
			Coarse	3mm	12 hours MIN