

EZYCOAT

RENDER • TEXTURE • PAINT

EZYCOAT RENDER RANGE

PRODUCT	APPLICATION TOOLS	FEATURE/BENEFIT	SAND GRADE	COVERAGE	RECOMMENDED COATING THICKNESS	POST APPLICATION
 SKIM RENDER Off White	Hawk & Steel Trowel Render Pump Sponge Float	Provides an even and consistent sand finish for use as a skim coat.	Medium Fine	3 - 4.8 m ² /bag	2.5mm MIN - 5mm MAX per coat to a MAX thickness of 8mm	48 hour set time 7 day cure Max strength at 28 days
 ECA RENDER Off White	Hawk & Steel Trowel Render Pump Sponge Float	Designed for multi-purpose use including EPS systems, with the addition of polymer for superior bonding strength.	Medium Fine	3 - 4.8 m ² /bag	2.5mm MIN - 5mm MAX per coat to a MAX thickness of 8mm	48 hour set time 7 day cure Max strength at 28 days
 PUMP RENDER Off White	Hawk & Steel Trowel Render Pump Sponge Float	Developed to cater for both hand and pump application.	Medium Coarse	3 - 4.8 m ² /bag	2.5mm MIN - 5mm MAX per coat to a MAX thickness of 8mm	48 hour set time 7 day cure Max strength at 28 days
 EZYFLOAT RENDER Off White	Hawk & Steel Trowel Sponge Float	Ideal for use under acrylic texture coatings.	Coarse	3 - 4.8 m ² /bag	2.5mm MIN - 5mm MAX per coat to a MAX thickness of 8mm	48 hour set time 7 day cure Max strength at 28 days
 EZYPREP & PATCH Off White	Steel Trowel	To prep and patch surfaces that would otherwise not accept a render product.	Fine	4 - 6 m ² /bag	1.5mm MIN 3mm MAX	48 hour set time 7 day cure Max strength at 28 days

TEXTURE FINISHES

PRODUCT	APPLICATION TOOLS	FEATURE/BENEFIT	SAND GRADE	COVERAGE	DRY TIME (SET TIME)
 SAND 800	Steel Trowel Plastic Float	A preblended acrylic texture that produces a granular sand finish style.	Medium	11 - 12 m ² /pail	Approx. 48 hours
 MIAMI	Steel Trowel Plastic Float	A mineral feature texture with the added protection of REPEL hydrophobic technology.	Medium	11 - 12 m ² /pail	Approx. 48 hours
 POLYMER RENDER	Steel Trowel Plastic Float	A medium-fine acrylic scrub fine sand finish.	Fine	7 - 10 m ² /pail	Approx. 48 hours
 SCRATCH 2MM	Steel Trowel Plastic Float	Decorative acrylic texture designed to produce a classic vertical or swirl finish.	Coarse Scratch	6 - 10 m ² /pail	Approx. 48 hours
 BASEFLEX	Steel Trowel Plastic Float	A granular base levelling coat or medium-coarse granular texture.	Coarse	3 - 5 m ² /pail/coat	Approx. 48 hours

SEALERS AND TOPCOATS

PRODUCT	APPLICATION TOOLS	FEATURE/BENEFIT	COVERAGE	DRY TIME (SET TIME)
 MASONRY SEALER	Roller Brush	Preparatory sealer and aid to subsequent texture application in EZYCOAT systems.	100 - 120 m ² /pail/coat	4 hours
 ULTRAFINE SEALER	Roller Brush	Preparatory sealer and aid to subsequent texture application in EZYCOAT systems.	70 - 85 m ² /pail per coat	4 hours
 CEILING TEXTURE INT/EXT	Texture Roller, Mop Finish Brush	A roll on stipple texture ideal for off-form concrete ceiling and soffits.	20 - 25 m ² /pail/coat	4 hours
 MEMBRANE	MIN 24mm Long Nap Roller Brush	A durable and flexible membrane paint designed to protect your EZYCOAT render & texture systems.	50 - 60 m ² /pail per coat 2 coats recommended	4 hours

PATCHES

PRODUCT	APPLICATION TOOLS	FEATURE/BENEFIT	SAND GRADE	PATCH DEPTH	DRY TIME (SET TIME)
 PATCH	Steel Trowel Sponge	Acrylic basecoat designed to patch and prepare masonry surfaces in EZYCOAT systems.	Smooth	2mm	12 hours MIN
			Coarse	3mm	12 hours MIN