

# EZYCOAT






RENDER • TEXTURE • PAINT

## TEXTURE, TOPCOAT, & PATCH RANGE GUIDE







Stock image used, final product finish may differ


## TEXTURE FINISHES

PRODUCT	APPLICATION TOOLS	FEATURE/BENEFIT	SAND GRADE	COVERAGE	DRY TIME (SET TIME)
 <b>SAND 800</b>	Steel Trowel Plastic Float	A preblended acrylic texture that produces a granular sand finish style.	Medium	11 - 12 m <sup>2</sup> /pail	Approx. 48 hours
 <b>MIAMI</b>	Steel Trowel Plastic Float	A mineral feature texture with the added protection of REPEL hydrophobic technology.	Medium	11 - 12 m <sup>2</sup> /pail	Approx. 48 hours
 <b>POLYMER RENDER</b>	Steel Trowel Plastic Float	A medium-fine acrylic scrub fine sand finish.	Fine	7 - 10 m <sup>2</sup> /pail	Approx. 48 hours
 <b>SCRATCH 2MM</b>	Steel Trowel Plastic Float	Decorative acrylic texture designed to produce a classic vertical or swirl finish.	Coarse Scratch	6 - 10 m <sup>2</sup> /pail	Approx. 48 hours
 <b>BASEFLEX</b>	Steel Trowel Plastic Float	A granular base levelling coat or medium-coarse granular texture.	Coarse	3 - 5 m <sup>2</sup> /pail/coat	Approx. 48 hours

## SEALERS AND TOPCOATS

PRODUCT	APPLICATION TOOLS	FEATURE/BENEFIT	COVERAGE	DRY TIME (SET TIME)
 <b>MASONRY SEALER</b>	Roller Brush	Preparatory sealer and aid to subsequent texture application in EZYCOAT systems.	100 - 120 m <sup>2</sup> /pail/coat	4 hours
 <b>ULTRAFINE SEALER</b>	Roller Brush	Preparatory sealer and aid to subsequent texture application in EZYCOAT systems.	70 - 85 m <sup>2</sup> /pail per coat	4 hours
 <b>CEILING TEXTURE INT/EXT</b>	Texture Roller, Mop Finish Brush	A roll on stipple texture ideal for off-form concrete ceiling and soffits.	20 - 25 m <sup>2</sup> /pail/coat	4 hours
 <b>MEMBRANE</b>	MIN 24mm Long Nap Roller Brush	A durable and flexible membrane paint designed to protect your EZYCOAT render & texture systems.	50 - 60 m <sup>2</sup> /pail per coat 2 coats recommended	4 hours

## PATCHES

PRODUCT	APPLICATION TOOLS	FEATURE/BENEFIT	SAND GRADE	PATCH DEPTH	DRY TIME (SET TIME)
 <b>PATCH</b>	Steel Trowel Sponge	Acrylic basecoat designed to patch and prepare masonry surfaces in EZYCOAT systems.	Smooth	2mm	12 hours MIN
			Coarse	3mm	12 hours MIN

For further information visit [activebuildingsystems.com.au](http://activebuildingsystems.com.au)  
or call **1300 566 592**